

RANDOM SET MODELS FOR THREE-PHASE ELECTRODE MATERIALS WITH AN EMPHASIS ON TRANSPORT RELEVANT CHARACTERISTICS

MATTHIAS NEUMANN

Institute of Stochastics, Ulm University

ABSTRACT. In this talk, parametric random closed set models are used to describe the complex microstructure of three-phase electrode materials observed by tomographic imaging. For this purpose, a model based on β -skeletons of Poisson point processes as well as a model based on excursion sets of two independent Gaussian random fields are considered. For both models, new relationships between model parameters and morphological characteristics are derived. Moreover, the models are fitted to 3D image data representing anodes in solid oxide fuel cells consisting of nickel, a certain ceramic phase and pores [1]. Model validation is performed with respect to the transport relevant microstructure characteristics mean geodesic tortuosity and constrictivity, *i.e.*, a geometrically defined radius of the characteristics bottleneck normalized by the median value of the continuous phase size distribution. These morphological characteristics have been recently defined for stationary random closed sets in [2], where properties of the corresponding estimators are discussed. Moreover, permeability of the pore space and effective conductivities of the solid phases are numerically simulated. This allows for an investigation of quantitative relationships between morphological characteristics and effective properties—an essential question in the field of heterogeneous materials [3]—for the considered anode materials. Additionally, it is shown that excursion sets of two correlated Gaussian random fields can be used to model the microstructure of gas-diffusion electrodes consisting of silver, polytetrafluorethylen and pores [4]. A method for parameter estimation by means of two-point cross-coverage probability functions is presented. After having fitted the model to 3D image data, model validation shows that mean geodesic tortuosity and the geometrically defined radius of the characteristic bottleneck are nicely reproduced.

REFERENCES

- [1] M. Neumann, B. Abdallah, L. Holzer, F. Willot, and V. Schmidt. Stochastic 3D modeling of three-phase microstructures for the prediction of transport properties in solid oxide fuel cells. *Transport in Porous Media*, 128:179–200, 2019.
- [2] M. Neumann, C. Hirsch, J. Staněk, V. Beneš, and V. Schmidt. Estimation of geodesic tortuosity and constrictivity in stationary random closed sets. *Scandinavian Journal of Statistics*, 46:848–884, 2019.
- [3] S. Torquato. *Random Heterogeneous Materials: Microstructure and Macroscopic Properties*. Springer, New York, 2002.
- [4] M. Neumann, M. Osenberg, A. Hilger, D. Franzen, T. Turek, I. Manke, and V. Schmidt. On a pluri-gaussian model for three-phase microstructures, with applications to 3D image data of gas-diffusion electrodes. *Computational Materials Science*, 156:325–331, 2019.